

**ATTACHING MAGNETIC BASE:**

(one-time installation)

1. Use a small portion (about the size of a grain of rice) from the provided putty, roll into a little ball to soften. Apply a thin layer evenly on the magnetic base using your thumbs to spread out. Make sure putty is applied on the correct side as labeled. Save the remaining putty for future use.
2. Remove or loosen strings. With your hand through the sound hole, find a location on the soundboard close to the bridge and away from braces and clear off any dust or wood shavings. Stick the magnetic base by applying light pressure with your finger for few seconds. You may also use the pickup on the outside. The magnetic force will help with the adhesion of the magnetic base.
3. If you need to change the location of the magnetic base, simply remove the base, roll the putty in a small ball to reactivate. Repeat steps 1 and 2.

**THE LOCATION WHERE YOU WILL ATTACH THE PICKUP IS VERY IMPORTANT FOR THE SOUND! EVERY INSTRUMENT IS DIFFERENT, AND THE „SWEET SPOT“ LOCATION WILL VARY FROM INSTRUMENT TO INSTRUMENT!**

Moving the magnetic base up or down the soundboard will affect the high-, mid- and low frequencies. Moving down toward treble strings will increase the high frequencies, and moving up towards the bass strings will increase your mid and low frequencies. Moving base closer to bridge will provide more clean and focused sound and moving further away from bridge will pickup more overtones and sound will be more resonant.

For a guitar with flat bridge, pickup may be used right on the bridge. For such installation you will need two magnetic bases (additional magnetic bases sold separately in 3-packs) to increase magnetic force to compensate for the extra thickness of bridge.

**YOUR GUITAR IS NOW READY TO USE THE PICKUP!**

**USING THE PICKUP:**

1. Plug in the mini jack into Pickup and plug guitar cable on other end of adapter. If your guitar is equipped with a strap pin, ALWAYS secure adapter to strap pin to avoid accidentally stepping on your cable and pulling out the pickup.

2. Make sure the silicone rubber pad on bottom of Pickup is always CLEAN to avoid scratching the finish. Place Pickup carefully on the soundboard until secured over the magnetic base. Do not drop on guitar! Follow this step every time you use the pickup.

3. Set the volume on your Pickup to about 50-70% and then adjust the gain and EQ on your amp. We recommend reducing low's and mid's and increase highs for more balanced sound. Avoid going above 80% on volume and/or GAIN at any time to reduce the risk of feedback.

4. If your amp is equipped with a PHASE switch, toggle the switch and choose the appropriate phase where you get a better sound and no feedback.

THE QUALITY OF YOUR SOUND CAN BE FURTHER ENHANCED IF CONNECTED TO A PRE-AMP AND/OR EFFECT PEDALS.

**WARNINGS AND PRECAUTIONS:**

- Always store the pickup and audio adapter inside the box when not in use.
- Always use two hands when connecting and disconnecting audio cable.
- Always clean the silicone pad before attaching to your instrument. Dirt and small particles may stick to it, which may scratch the finish of your instrument.

**WARNING:** THIS IS NOT A TOY! MAGNETS ARE VERY STRONG AND BRITTLE IF HIT HARD. BROKEN MAGNETS ARE SHARP. DISCARD IF BROKEN. DO NOT INGEST OR INHALE. SWALLOWED MAGNETS CAN STICK TO INTESTINES CAUSING SERIOUS INJURY OR EVEN DEATH. SEEK IMMEDIATE MEDICAL ATTENTION. KEEP AWAY FROM PACEMAKERS AND INTERNAL MEDICAL DEVICES. MAGNETIC MEDIA AND ELECTRONIC EQUIPMENT HAZARD.